

gutter connector - robust

Image	Product description	Technical details																			
	<ul style="list-style-type: none"> ■ with safety and flexible Z-Spring ■ fit in accordance to DIN 18461 ■ product for the simple Click-On System ■ demountable and reusable ■ sealing element for permeable gutter overlaps ■ high-quality optical characteristic ■ consistent shape and exact fit accuracy ■ ensures additional expansion 	<p>Available dimensions:</p> <p>400, 333, 280, 250</p> <p>Materials:</p> <table border="1" style="width: 100%; border-collapse: collapse; border-style: dashed;"> <tr style="background-color: #cccccc;"><td>TECU® Copper</td></tr> <tr style="background-color: #cccccc;"><td>VM Blank-Zinc®</td></tr> <tr style="background-color: #cccccc;"><td>galvanized</td></tr> <tr style="background-color: #cccccc;"><td>galvanized coated robust</td></tr> </table> <p>Measurements:</p> <table border="1" style="width: 100%; border-collapse: collapse; border-style: dashed;"> <thead> <tr style="background-color: #cccccc;"> <th>size</th> <th>R1</th> <th>R2</th> </tr> </thead> <tbody> <tr><td>400</td><td>96</td><td>9</td></tr> <tr><td>333</td><td>76,5</td><td>9</td></tr> <tr><td>280</td><td>63,5</td><td>9</td></tr> <tr><td>250</td><td>52,5</td><td>9</td></tr> </tbody> </table>	TECU® Copper	VM Blank-Zinc®	galvanized	galvanized coated robust	size	R1	R2	400	96	9	333	76,5	9	280	63,5	9	250	52,5	9
TECU® Copper																					
VM Blank-Zinc®																					
galvanized																					
galvanized coated robust																					
size	R1	R2																			
400	96	9																			
333	76,5	9																			
280	63,5	9																			
250	52,5	9																			
2D-Drawing																					
	<table border="1" style="width: 100%; border-collapse: collapse; border-style: dashed;"> <thead> <tr style="background-color: #0056b3; color: white;"> <th colspan="2" style="text-align: center;">Material standards</th> </tr> </thead> <tbody> <tr style="background-color: #cccccc;"><td>Copper, Copper alloy</td><td>DIN EN 1172</td></tr> <tr style="background-color: #cccccc;"><td>Zinc, Zinc alloy</td><td>DIN EN 988</td></tr> <tr style="background-color: #cccccc;"><td>Fit</td><td>DIN 18461</td></tr> </tbody> </table>	Material standards		Copper, Copper alloy	DIN EN 1172	Zinc, Zinc alloy	DIN EN 988	Fit	DIN 18461												
Material standards																					
Copper, Copper alloy	DIN EN 1172																				
Zinc, Zinc alloy	DIN EN 988																				
Fit	DIN 18461																				

gutter connector - robust

Article number:

size	TECU® Copper	VM Blank- Zinc®	galvanized	galvanized coated robust
400	115800	135800	125800	145800
333	115805	135805	125805	145805
280	115810	135810	125810	145810
250	115815	135815	125815	145815

Packaging information:

size	pieces per box
400	10
333	10
280	10
250	10