



**downpipe**

Image	Product description	Technical details																																																																		
	<ul style="list-style-type: none"> <li>■ seamed with inside beading or welded* (see material chart)</li> <li>■ top end with socket</li> <li>■ consistent shape and fit accuracy</li> <li>■ high-quality optical characteristic</li> </ul>	<p><b>Available dimensions:</b></p> <p>150, 120, 100, 80, 60                      Length: 2000 mm / 3000mm</p> <p>regional are downpipes with the sizes 76 and 87 usual.</p> <p><b>Materials:</b></p> <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr style="background-color: #D3D3D3;"> <th></th> <th>60</th> <th>80</th> <th>100</th> <th>120</th> <th>150</th> </tr> </thead> <tbody> <tr> <td>* TECU® Copper</td> <td>0,60</td> <td>0,60</td> <td>0,60</td> <td>0,70</td> <td>0,70</td> </tr> <tr> <td>* VM Blank-Zinc®</td> <td>0,65</td> <td>0,65</td> <td>0,65</td> <td>0,70</td> <td>0,70</td> </tr> <tr> <td>galvanized</td> <td>0,60</td> <td>0,60</td> <td>0,60</td> <td>0,70</td> <td>0,70</td> </tr> <tr> <td>galvanized coated robust</td> <td>0,60</td> <td>0,60</td> <td>0,60</td> <td>0,70</td> <td>0,70</td> </tr> <tr> <td>Ugitop®</td> <td>0,50</td> <td>0,50</td> <td>0,50</td> <td>0,60</td> <td>0,60</td> </tr> <tr> <td>Uginox FTE®</td> <td>0,50</td> <td>0,50</td> <td>0,50</td> <td>0,60</td> <td>0,60</td> </tr> </tbody> </table> <p>*these pipes are welded</p> <p><b>Measurements:</b></p> <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr style="background-color: #D3D3D3;"> <th>size</th> <th>D1</th> <th>D2</th> <th>S</th> </tr> </thead> <tbody> <tr> <td>150</td> <td>150+1</td> <td>149</td> <td>0,60 - 0,70</td> </tr> <tr> <td>120</td> <td>120+1</td> <td>119</td> <td>0,60 - 0,70</td> </tr> <tr> <td>100</td> <td>100+1</td> <td>99</td> <td>0,50 - 0,65</td> </tr> <tr> <td>80</td> <td>80+1</td> <td>79</td> <td>0,50 - 0,65</td> </tr> <tr> <td>60</td> <td>60+1</td> <td>59</td> <td>0,50 - 0,65</td> </tr> </tbody> </table>		60	80	100	120	150	* TECU® Copper	0,60	0,60	0,60	0,70	0,70	* VM Blank-Zinc®	0,65	0,65	0,65	0,70	0,70	galvanized	0,60	0,60	0,60	0,70	0,70	galvanized coated robust	0,60	0,60	0,60	0,70	0,70	Ugitop®	0,50	0,50	0,50	0,60	0,60	Uginox FTE®	0,50	0,50	0,50	0,60	0,60	size	D1	D2	S	150	150+1	149	0,60 - 0,70	120	120+1	119	0,60 - 0,70	100	100+1	99	0,50 - 0,65	80	80+1	79	0,50 - 0,65	60	60+1	59	0,50 - 0,65
	60	80	100	120	150																																																															
* TECU® Copper	0,60	0,60	0,60	0,70	0,70																																																															
* VM Blank-Zinc®	0,65	0,65	0,65	0,70	0,70																																																															
galvanized	0,60	0,60	0,60	0,70	0,70																																																															
galvanized coated robust	0,60	0,60	0,60	0,70	0,70																																																															
Ugitop®	0,50	0,50	0,50	0,60	0,60																																																															
Uginox FTE®	0,50	0,50	0,50	0,60	0,60																																																															
size	D1	D2	S																																																																	
150	150+1	149	0,60 - 0,70																																																																	
120	120+1	119	0,60 - 0,70																																																																	
100	100+1	99	0,50 - 0,65																																																																	
80	80+1	79	0,50 - 0,65																																																																	
60	60+1	59	0,50 - 0,65																																																																	
<b>2D-Drawing</b>	<b>Material standards</b>																																																																			
	<table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <tbody> <tr style="background-color: #D3D3D3;"> <td>Copper, Copper alloy</td> <td>DIN EN 1172</td> </tr> <tr style="background-color: #D3D3D3;"> <td>Zinc, Zinc alloy</td> <td>DIN EN 988</td> </tr> </tbody> </table>	Copper, Copper alloy	DIN EN 1172	Zinc, Zinc alloy	DIN EN 988																																																															
Copper, Copper alloy	DIN EN 1172																																																																			
Zinc, Zinc alloy	DIN EN 988																																																																			

**downpipe**

**Article number:**

size	TECU® Copper	VM Blank- Zinc®	galvanized	galvanized coated robust	Ugitop®	Uginox FTE®
150	117915	137915	127915	147915		177915
120	117912	137912	127912	147912		177912
100	117910	137910	127910	147910	217910	177910
80	117980	137980	127980	147980	217980	177980
60	117960	137960	127960	147960		

**Tender specification:**

supply and install.....  
 Downpipes (orbital) according to DIN EN 612,  
 Material like gutter.  
 Mounting with brackets with screw top.  
**Size - 80 - 100 - 120 - 150 - mm,**  
 Incl. required elbows, made of pipe,  
 and pipe cover  
 Brand Zambelli or equivalent