

box outlet

Image	Product description	Technical details																																																																												
	<ul style="list-style-type: none"> ■ with patented strengthened bend and eye ■ with compass card ■ high-quality optical characteristic ■ consistent shape and exact fit accuracy 	<p>Available dimensions:</p> <p>500/150 400/120 333/100 280/87, 280/80 250/80, 250/76 200/60</p> <p>Materials:</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td>TECU® Copper</td><td style="text-align: right;">0,6</td></tr> <tr><td>VM Blank-Zinc®</td><td style="text-align: right;">0,7</td></tr> <tr><td>VM Quartz-Zinc®</td><td style="text-align: right;">0,7</td></tr> <tr><td>VM Anthra-Zinc®</td><td style="text-align: right;">0,7</td></tr> <tr><td>galvanized</td><td style="text-align: right;">0,6</td></tr> <tr><td>galvanized coated robust</td><td style="text-align: right;">0,65</td></tr> <tr><td>Uginox FTE®</td><td style="text-align: right;">0,5</td></tr> <tr><td>Aluminium</td><td style="text-align: right;">0,7</td></tr> </table>	TECU® Copper	0,6	VM Blank-Zinc®	0,7	VM Quartz-Zinc®	0,7	VM Anthra-Zinc®	0,7	galvanized	0,6	galvanized coated robust	0,65	Uginox FTE®	0,5	Aluminium	0,7																																																												
TECU® Copper	0,6																																																																													
VM Blank-Zinc®	0,7																																																																													
VM Quartz-Zinc®	0,7																																																																													
VM Anthra-Zinc®	0,7																																																																													
galvanized	0,6																																																																													
galvanized coated robust	0,65																																																																													
Uginox FTE®	0,5																																																																													
Aluminium	0,7																																																																													
2D-Drawing	Material standards																																																																													
	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td>Copper, Copper alloy</td><td style="text-align: right;">DIN EN 1172</td></tr> <tr><td>Zinc, Zinc alloy</td><td style="text-align: right;">DIN EN 988</td></tr> </table>	Copper, Copper alloy	DIN EN 1172	Zinc, Zinc alloy	DIN EN 988	<p>Measurements:</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>size</th> <th>A</th> <th>B</th> <th>C</th> <th>D</th> <th>E</th> <th>F</th> <th>d</th> </tr> </thead> <tbody> <tr><td>500/150</td><td>210</td><td>175</td><td>185</td><td>60</td><td>13</td><td>200</td><td>150</td></tr> <tr><td>400/120</td><td>175</td><td>112</td><td>90</td><td>40</td><td>13</td><td>150</td><td>120</td></tr> <tr><td>333/100</td><td>145</td><td>104</td><td>76</td><td>40</td><td>13</td><td>120</td><td>100</td></tr> <tr><td>280/87</td><td>136</td><td>90</td><td>60</td><td>35</td><td>12</td><td>100</td><td>87</td></tr> <tr><td>280/80</td><td>120</td><td>80</td><td>50</td><td>35</td><td>12</td><td>100</td><td>80</td></tr> <tr><td>250/80</td><td>118</td><td>80</td><td>50</td><td>35</td><td>12</td><td>85</td><td>80</td></tr> <tr><td>250/76</td><td>123</td><td>80</td><td>52</td><td>30</td><td>12</td><td>85</td><td>76</td></tr> <tr><td>200/60</td><td>89</td><td>54</td><td>40</td><td>30</td><td>12</td><td>70</td><td>60</td></tr> </tbody> </table>	size	A	B	C	D	E	F	d	500/150	210	175	185	60	13	200	150	400/120	175	112	90	40	13	150	120	333/100	145	104	76	40	13	120	100	280/87	136	90	60	35	12	100	87	280/80	120	80	50	35	12	100	80	250/80	118	80	50	35	12	85	80	250/76	123	80	52	30	12	85	76	200/60	89	54	40	30	12	70	60
Copper, Copper alloy	DIN EN 1172																																																																													
Zinc, Zinc alloy	DIN EN 988																																																																													
size	A	B	C	D	E	F	d																																																																							
500/150	210	175	185	60	13	200	150																																																																							
400/120	175	112	90	40	13	150	120																																																																							
333/100	145	104	76	40	13	120	100																																																																							
280/87	136	90	60	35	12	100	87																																																																							
280/80	120	80	50	35	12	100	80																																																																							
250/80	118	80	50	35	12	85	80																																																																							
250/76	123	80	52	30	12	85	76																																																																							
200/60	89	54	40	30	12	70	60																																																																							

box outlet

Article number:

size	TECU® Copper	VM Blank- Zinc®	VM Quartz- Zinc®	VM Anthra- Zinc®	galvanized	galvanized coated robust	Uginox FTE®	Aluminium
500/150	110800	130800			120800			150800
400/120	110805	130805			120805	140805	170805	150805
333/100	110815	130815	180815	230815	120815	140815	170815	150815
280/87	110840	130840						
280/80	110850	130850			120850	140850		150850
250/80	110855	130855			120855	140855	170855	150855
250/76	110858	130858						
200/60	110865	130865	180865	230865	120865			150865

Packaging information:

size	pieces per box
500/150	1
400/120	25
333/100	25
280/87	25
280/80	25
250/80	25
250/76	25
200/60	25

Tender specification:

supply and install.....

Box outlet, with strengthened bend and eye,
 welded on backside, with compass rose, as allowance to gutter,

Sizes: 500/150 mm 280/80 mm
 400/120 mm 250/80 mm
 333/100 mm 250/76 mm
 280/87 mm 200/60 mm

Brand Zambelli or equivalent