


P:\RR-RIB-ROOF\03_Produkte\Regeldetails\EN.C. rigid insulation board with clip border flat\RIB-ROOF Speed 500\C1.1.1.01 with clip border (flat)\C1.1.1.01.dwg

fixed point with
aluminium rivet



RIB-ROOF Speed 500

clip border (flat or profiled)
turned directional clip or
turned directional profile

Detail fixed point
scale 1:2

build up:

RIB-ROOF Speed 500
protective layer
(optional)
rigid insulation
board
vapour barrier

ridge cap

RIB-ROOF folded up at ridge side


closure

profile filler - top side


fixed point (acc. statics requirement)

clip border (flat)

omega profile for fixed point
(acc. statics requirement)



alternative: ventilation ridge
ventilation cross-section 450 cm²/m



title
**double pitch roof
with clip border (flat)**

RIB-ROOF
metalldachsysteme

Zambelli RIB-ROOF GmbH & Co. KG
Hans-Sachs-Str. 3+5, D-94569 Stephansposching
Tel. +49 (0)9931 89590-0
Fax +49 (0)9931 89590-49
e-mail: rib-roof@zambelli.de

System
RIB-ROOF Speed 500

ridge	drawn by T.W.	scale 1:5
drawing nr. C.1.1.1.01	index -	date 03.04.12
		format A3

zambelli

This drawing is copyright and remains the property of Zambelli. It must not be reproduced, used, disclosed or transmitted to third parties in any form, in whole or in part, without prior written permission.