



3D view  
without scale

front view  
(assembly)  
M 1:1

Dimension of the fastening screws  
(no countersunk): screw head height  
max. 5,50mm

screwdriver  
with long bit socket

cutting = 125mm

|  |                                  |  |                  |                       |
|--|----------------------------------|--|------------------|-----------------------|
| title<br><b>fixed point profile<br/>for RIB-ROOF 465</b> | System<br><b>RIB-ROOF 465</b>    |  |                  |                       |
|  | <b>system accessories</b>        |  | drawn by<br>T.W. | scale<br>1:1/no scale |
|  | drawing nr.<br><b>Z.2.1.5.01</b> | index<br><b>A</b>  | date<br>21.06.12 | format<br>A3          |
| <b>RIB-ROOF</b><br>metalldachsysteme                     |                                  | Zambelli RIB-ROOF GmbH & Co. KG<br>Hans-Sachs-Str. 3+5, D-94569 Stephansposching<br>Tel. +49 (0)9931 89590-0<br>Fax +49 (0)9931 89590-49<br>e-mail: rib-roof@zambelli.de   |                  |                       |
|  |                                  | <br><small>This drawing is copyright and remains the property of Zambelli. It must not be reproduced, used, disclosed or transmitted to third parties in any form, in whole or in part, without prior written permission.</small> |                  |                       |